

DINGLI

Exceed · New Height



DH0825ERT

ZHEJIANG DINGLI MACHINERY CO., LTD.

ADD:188 Qihang Road, Leidian Town, Deqing, Zhejiang, P.R.C

P.C:313219

Tel:+86-572-8681688

E-Mail:export@cndingli.com

Https://www.cndingli.com

As the technology is constantly updated, technical parameters are subject to change without notice. This brochure is for reference only.
The copyright is owned by Zhejiang Dingli. No content may be copied or plagiarized for any purpose without written permission.
October 2024 edition

DH0825ERT

Robot Body Parameter

Model	SR50-2180
Degrees of Freedom	6
Wrist Load	50kg - 110lb
Max. Working Radius	2180.5mm - 7ft 2in
Body Weight	560kg - 1235lb
Repeat Positioning Accuracy	±0.1mm
Noise Level	< 80dB(A)
Operating Temperature	0°C~+55°C
Humidity	Below 75% RH(Short-term 75%RH)
Body Protection	IP40(Wrist IP65)

Robot Joint Angle/Speed

J1	±160° / 140°/S
J2	+160°~-60° / 120°/S
J3	+75°~195° / 120°/S
J4	±185° / 220°/S
J5	±120° / 220°/S
J6	±360° / 320°/S

Free Stop Time/Free Stop Distance

J1	0.42S / 26°
J2	0.65S / 33°
J3	0.25S / 20°
J4	0.29S / 26°
J5	0.29S / 26°
J6	0.19S / 19°

3D Camera

Power	24VDC
Optimal Working Distance	1900±700mm
Max. Working Distance	2600mm
Repeat Accuracy	±2@1900mm
Waterproof Rating	IP65

Standardized Parameters

Max. Horizontal Drilling Height	7.20m - 23ft 7in
Max. Vertical Upward Drilling Height	8.00m - 26ft 3in
Min. Horizontal Drilling Height	2.00m - 6ft 7in
Min. Vertical Downward Drilling Height	0.80m - 2ft 7in
Overall Width(Stowed)	2.50m - 8ft 2in
Overall Height(Stowed)	2.65m - 8ft 8in
Overall Length(Stowed)	5.58m - 18ft 4in
Tailswing	0
Main Boom Maximum Angle	75°
Ground Clearance	0.41m - 1ft 4in
Wheelbase	2.80m - 9ft 2in
Tyres	385/45-28
Travel Speed(Stowed)	≥6.0km/h - 3.73mph
Travel Speed(Raised)	≥1.1km/h - 0.68mph

Punching Impact Drill

Branding	BOSCH
Model	GBH12-52D/GBH12-52DV
Type	Five-pit Electric Hammer
Rated Input Power	1700W
Rated Voltage	220VAC
Single Hammer Force	19J
Rated Speed	220rpm
Max. Hole Diameter	52mm - 2in
No-Load Speed	0~220rpm
Application Range	Concrete

Punching Parameters

Drilling Positioning Mode	Center Mode/Marker Mode
Number of Holes	Single Point Punching/Batch Group Punching
Drilling Stroke/Drilling Speed	300mm / 1-5mm/s 1ft / 0.04in-0.20in/s
Drilling Stroke Repeatability	±2mm - ±0.08in
Max. Drilling Space Diameter	2000mm - 6ft 7in
Vertical Incline Angle of Drilling Space	-90°~+90°
Drilling Space Repeatability	±0.2mm - ±0.01in
Power	< 4kW
Max. Static Load	< 300kg

Power System

Weight	180kg - 3971lb
Protection Rating	IP54
Rated Input Power	Three-phase Five-wire 380VAC
Power Capacity	8kVA
Rated Current	12A
Ambient Temperature	0°C~+40
Operating Humidity	45~80%RH
Control Circuit	24VDC
Industrial PC Power	12V
Display Power	24V

Gradeability	30%
Maxi. Chassis Angle	X-5°/Y-5°
Turret Rotation	360° Continuous
Max. Wind Speed	12.5m/s - 41ft/s
Turning Radius(Inside/Outside)	1.87m/3.22m - 6ft 2in/10ft 7in
Battery	520Ah/80V
Charger	90-264VAC/6.6kW
Driving Motor	18kW/3243rpm
Lifting Motor	24kW/2150rpm
Inverter	GPLS1580i-PY-01
Remote Control	autec: DJM-CRD-DL
Remote Receiver	autec: DJM-CRD-DL
Hydraulic Tank	165L - 43gal
Overall Weight	10500kg - 23148lb